

ACCESSORIES

KP, KL, Series 【KP-AUXA, KP-AUX1T, KP-VAR, KP-VA1, KP-AUX2, KP-AUX5】
【KL-SSB, KL-1, KL-2, KL-3】



KP-AUXA, KP-AUX1T



Auxiliary Arm

KP-AUXA, KP-AUX1T

- Provide with the rocker arm , enable to revolve on 360 degrees.
- Main shaft can be extended to maximum 830mm
- Power arm inside includes nitrogen gas stick , allow user to grab the arm easily, automatic lift up to position after finishing the work .
- Easy to assemble and Disassemble.
- Optional accessory KP-VA1, KP-VAR(90 degree adapter) is available for user to Adjust angle in accordance with the object to be fastened.

KP-AUX2, KP-AUX5

- Main shaft can be extended to maximum 340mm
- Steady bearing in horizontal direction for screwdriver to act in vertical precisely.
- Utilize KL-1200 to suspend the spring hoist vertically and capable of making adjustment at screwdriver's weight.
- Steady screwdriver with 4 sides of plate , the screwdriver head of horizontal and vertical position becomes more accurate.
- Applying to low torque , high precision screwdriver, most suitable for small objects.



KP-VAR, KP-VA1

Specifications

Model	KP-AUXA	KP-AUX1T	KP-AUX2	KP-AUX5
Description	Suspension Arm	Suspension Arm	Suspension Rope	Suspension Rope
Reach	50mm~830mm	50mm~830mm	50mm~340mm	50mm~340mm
Applicable Models	SKD-RB60L/P SKD-RB90L/P SKD-RB120L/P SKD-RB180L/P	SK-8 Series SK-9 Series SKD-8000 Series SKD-B800 Series SKD-BE800 Series	SKD-2000L SKD-2200L SKD-2300L SKD-B200 Series SKD-BC200 Series	SKD-B500 Series SKD-BC500 Series SKD-BE500 Series SKD-5000 Series
Remark	KP-VAR adaptable	KP-VA1 adaptable	Spring Balancer KL-1200 adaptable	Spring Balancer KL-1200 adaptable

※ The auxiliary arm can be used only with Kilews electric screwdrivers.

**KP-AUX2
KP-AUX5**



KL-SSB

Slow Start Control Module

KL-SSB

- The BYPASS system is able to cancel the slow motion operation when counter-clockwise rotation is detected.
- Easily loosening the screws reversely.
- Rotation in the slow motion is 30%-100% comparing to regular rotation.
- Selection of adjusting stages: L1-L2-L3 -...L9-L0-L1.
- Supplying the output signals of start /break/rotation in clock or counter-clockwise.
- Applying to any non-carbon-brush series of Kilews
- the operation of slow motion time can be adjusted to 0.1~5.0secs.
- Dimension 58X95X35mm(LXWXH)

90° Degree Attachment Applicable Model

KL-1	SKD-B830L, SKD-B850L, SKD-7000L, SKD-7200L, SKD-7800L, SKD-8300L, SKD-8400L, SKD-8500L, SKD-B730L SK-8130L, SK-8230L, SK-8140L, SK-8240L, SK-8150L, SK-8250L, SK-9131L, SK-9231L, SK-9130L, SK-9230L, SK-9140L, SK-9240L, SK-9150L, SK-9250L,
KL-2	SKD-5200L, SK-3220L, SK-3180L, SKD-B512L SKD-5300L, SK-3120L, SK-3280L, SKD-B519L
KL-3	SKD-RB60L, SKD-RB90L, SKD-RB150L, SKD-RB180L Applying for B type or W type.

※ Only for "L" trigger start screwdrivers

90° Degree Attachment

**90° Degree
Attachment
KL-1**



KL-2



KL-3

